

KNOWLEDGE BASE · PUBLIC DOCUMENT

Off-site backups: sending a copy to cloud storage, an S3 bucket or Google Drive

Backups & Migration

CODE

RLX-MZ-KB-1233

VERSION

v2026.10.18

COUNTRY · LANGUAGE

Mozambique · English

MozOut Mozambique

RLX Holdings, S.A. · Group RLX Holdings

Tax ID (NUIT) 401 191 607 · Legal entity no. (NUEL) 105 045 974 · Economic activity code (CAE) 62022

<https://www.meu.mozout.co.mz/knowledgebase/1233>

Off-site backups: sending a copy to cloud storage, an S3 bucket or Google Drive

 Backups & Migration Created on **October 10, 2026** Updated on **October 18, 2026** 4 min read

An **off-site** copy is the one that survives losing the account. There are five ways to get one out: a **WordPress backup plugin** with a cloud destination, a backup program running on **your computer or a VPS** (rclone is the best known), the remote-destination option of the full cPanel backup where it exists, a **script with rsync or SFTP**, or simply downloading and uploading by hand. This is the mechanics; prices and conditions are those of the storage provider you choose.

Where to send it

Destination	What it is	What you need to know
S3-compatible object storage	A “bucket” in a provider’s account, used by programs.	Four details: the service address (endpoint), the region, the access key and the secret key, plus the bucket name.
Google Drive and similar file services	A folder in a personal or company account.	Authorisation is done by a one-time sign-in that gives the program renewable access. See saving files to Google Drive automatically .
Another server, over SFTP	A disk of yours, on another machine.	The address, the user and an SSH key. See automatic file transfers with SFTP and rsync .
An external disk or the computer	The local copy, not truly “off-site” if it is in the same room.	A disk kept at another address counts as off-site.

Step by step

- 1 Choose the destination** and create the account or bucket. If the provider allows it, turn on **keeping old versions**: it protects you from a damaged copy overwriting the good one.

- 2 **Create a key just for this.** Give it permission only on that bucket or folder, and never use the account's main key.
- 3 **Test with a small file** before automating. See that it arrived, that it opens and that the size matches.
- 4 **Automate.** With a plugin, it is the plugin's own "destination" option. With rclone, a command scheduled in `cron` (**cron jobs**). Pick a quiet hour.
- 5 **Check every week, for the first few weeks**, that the day's file shows up at the destination. It is the commonest silent failure.
- 6 **Add an alert** in case the copy fails, so you do not find out only when you need it. See **getting an alert when something fails**.

➞ An example with rclone

rclone is a free, open-source third-party program; we do not sell it and support does not install or repair it (**how far our support goes**). It runs on your computer or on a VPS. First you set the destination up interactively, then you copy:

```
rclone config
rclone copy /path/to/backups remote:bucket-name/site --dry-run
rclone copy /path/to/backups remote:bucket-name/site --progress
```

The first line creates a destination under a name you choose (here, "remote"). The second, with `--dry-run`, only shows what it would do. The third copies. To read the backups from your shared account, rclone connects over SFTP; use the SSH address and port your panel shows.

! "Copy" and "sync" are not the same.
Rclone `copy` adds to the destination. `rclone sync` makes the destination match the source, **deleting** there whatever no longer exists here. If you delete a file by mistake and sync, it is deleted from the copy too. For backups, use `copy`.

! Access keys are worth money and data.
Keep them in a file with permission 600, outside `public_html`, and never in a public repository. If one gets exposed, delete it at the provider and create another.

💡 Think about where the data sits.
If the copy holds customers' personal data, the storage provider's country is a privacy decision, not just a price one. See **data protection on your website**.

 NEED A HAND?

Have the destination but the copy does not arrive, or not sure where to start? Tell us what you use.

 **Open a support ticket** →

 Where to see it in your account

Every hosting plan has an automatic daily backup with restores at no cost. In cPanel, look under **JetBackup** (or the backups screen): it lists the restore points available for your account. That copy is ours and does not replace one you keep elsewhere, which is the point of this article. Whether your cPanel offers a remote destination for the full backup is something to read on screen, on the backup page, which shows the options your account has. If none suits you, the other routes in the article remain valid: a plugin with a cloud destination, rclone from your computer or from a VPS, or downloading and uploading by hand. All our hosting plans include SSH (Terminal and SSH Access in cPanel, port 2299), so rclone can read the copies over SFTP.

 SEE ALSO

The 3-2-1 backup rule for a website



Copying files to another server with rsync, safely



Saving files to Google Drive automatically



Automatic backups of your own application: cron and mysqldump





MozOut Mozambique

RLX Holdings, S.A. · Group RLX Holdings

TAX ID (NUIT)	401 191 607
LEGAL ENTITY NO. (NUEL)	105 045 974
ECONOMIC ACTIVITY CODE (CAE)	62022
REGISTERED OFFICE	Bairro 7 de Setembro Vilankulo 1304 · CEP 0411-02, Inhambane, Mozambique
CONTACT	info@mozout.co.mz · +258 84 635 1111 · +258 86 635 1111 · www.mozout.co.mz
OPENING HOURS	Monday to Friday - 08 AM to 04 PM Saturday & Sunday - Closed



Online version of this document

RLX-MZ-KB-1233 · v2026.10.18 · Generated on 21/10/2026 17:42