Mozout

Generated on 13/11/2026 19:51

KNOWLEDGE BASE · PUBLIC DOCUMENT

Importing our API into Insomnia and other API clients, and setting the Bearer key

WhatsApp & APIs


CODE	VERSION	COUNTRY · LANGUAGE
RLX-MZ-KB-2735	v2026.11.13	Mozambique · English

MozOut Mozambique
RLX Holdings, S.A. · Group RLX Holdings
Tax ID (NUIT) 401 191 607 · Legal entity no. (NUEL) 105 045 974 · Economic activity code (CAE) 62022

https://www.meu.mozout.co.mz/knowledgebase/2735

Importing our API into Insomnia and other API clients, and setting the Bearer key

WhatsApp & APIs Created on **November 13, 2026** 2 min read



The short answer: Insomnia, like most API clients, imports our OpenAPI specification and creates every request in one go. What changes from one client to the next is the name of the menus; the steps are the same: **import, put the key in a variable, authenticate with Bearer, and test**.

In Insomnia

1. **Have the specification ready:** the link is in the API reference, Specification section, or download the `openapi.json` file.
2. **Use the Import option** and choose to import from a link or from a file. Insomnia recognises the OpenAPI format and creates the requests.
3. **Create an environment** with a variable for the key, for example `rlx_api_key`, holding your `sandbox_` key.
4. **In the auth settings** of the requests, or of the folder that groups them, choose Bearer Token and use the variable, for example `{{ _.rlx_api_key }}`.
5. **Test** with `GET /v1/ping`, which needs no key, and then with `GET /v1/token`.

In other clients

Clients such as Bruno and Hoppscotch also import OpenAPI specifications. Look for the import option, choose OpenAPI and follow the same order. In all of them, authentication is the same: the `Authorization: Bearer` header followed by the key.

If the import fails

Symptom	What to try
The client says it does not recognise the version	The specification is OpenAPI 3.1. Update the client: older versions of some tools only read 3.0.
Importing from the link does not work	Download the file and import it from disk.
Requests go to the wrong address	Check the base address in the environment or collection. The paths already start with `/v1`.
`401` **error**	The key is missing, mistyped, revoked or expired. Check that the variable has a value in the active environment.

A desktop client keeps the key in its own data.
Use a `sandbox_` key for testing, do not export collections with the key, and if you share it by mistake, revoke it: **what to do, in the right order**.

Prefer Postman?
Its steps, with the right variables, are in **importing the API into Postman**.

RECOMMENDED

The specification link is at the end of the API reference.

See the specification →

SEE ALSO

- **Importing our API into Postman from the OpenAPI specification, step by step** →
- **The OpenAPI specification of our API: what it is, where to download it and what it contains** →
- **Generating an API client for your language from our OpenAPI specification** →
- **Your key in the API Playground: where it stays, why sandbox_ first, and the prod_ warning** →

An API key or token has leaked: what to do, in the right order →

MozOut Mozambique

RLX Holdings, S.A. · Group RLX Holdings

TAX ID (NUIT)	401 191 607
LEGAL ENTITY NO. (NUEL)	105 045 974
ECONOMIC ACTIVITY CODE (CAE)	62022
REGISTERED OFFICE	Bairro 7 de Setembro Vilankulo 1304 · CEP 0411-02, Inhambane, Mozambique
CONTACT	info@mozout.co.mz · +258 84 635 1111 · +258 86 635 1111 · www.mozout.co.mz
OPENING HOURS	Monday to Friday - 08 AM to 04 PM Saturday & Sunday - Closed

Online version of this document

RLX-MZ-KB-2735 · v2026.11.13 · Generated on 13/11/2026 19:51